




N-Channel Enhancement Mode Field Effect Transistor



SOT-23



Product Summary



General Description

Applications

12V Automotive systems

Absolute Maximum Ratings

Parameter	Symbol	Limit	Unit
		±	
			°C
		~	°C







Ordering Information

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE









YJL02N04AKHQ

■ Typical Performance Characteristics







YJL02N04AKHQ






YJL02N04AKHQ






YJL02N04AKHQ


SOT-23 Package Outline Dimensions




TOP VIEW



SIDE VIEW




SIDE VIEW



SUGGESTED SOLDER PAD LAYOUT

SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.020	0.300	0.500
θ	0°	8°	0°	8°

Marking Information





YJL02N04AKHQ

Disclaimer
